

OAK ASKANIA MOLTI



Supplier	Barlinek S.A.
Product number	BC1-DBE3-LIN-XXX-D14207-F
Catalog number	3WG000311
EAN Code	5906737986271

MATERIAL/APPERANCE

Product description:	Product consists of three layers: surface layer – oak, middle and bottom layer - pine
Top layer:	Three rows of strips, Family grade
Finish surface Layer:	5 layers of acrylic semi matt lacquer UV professional hardened (3 layers of primer lacquer – 2 layers of UV hardened surface ceramic lacquer
The connection system boards: (for each package includes instructions assembly)	Cross edge - Barlock 5Gc system, transverse lock insert - Plywood

CHARACTERISTICS OF THE SURFACE LAYER

Surface appearance	Yellow-brown oak wood with natural features characteristic for this kind. The floor is characterized by grain variability and varied colours. It darkens under the influence of UV rays
Hardness oak applied to the top layer of the board. The method according EN 13489 – testing Brinell (EN 1534)	Average hardness 37 MPa

Dimensional characteristics and acceptable deviations (consistent with standard PN-EN 13489). Dimensional characteristics and dimensional tolerances, marked at the time of leaving the manufacturer’s facility, given in accordance with the type of multi-layer flooring elements.

PRODUCT SPECIFICATION

CARE OF LACQUERED FLOORS	
PROTEKTOR CONCENTRATE - Agent for everyday floor care	PROPERTIES: Concentrated floor cleaning agent with natural care additives. Deep cleans without smudging. Refreshes the floor and protects it against dirt. APPLICATION: For all types of lacquered wooden floors. May also be used for other lacquered surfaces, e.g. furniture or worktops in rooms, as well as for laminated floors. <ul style="list-style-type: none"> Yield approx. 500m² /1 L
PROTEKTOR COMPLETE Agent for thorough periodic cleaning of the floor	PROPERTIES: Liquid agent for cleaning all lacquered wooden surfaces. APPLICATION: For all indoor lacquered wooden floors. <ul style="list-style-type: none"> Yield approx. 200m²/l IMPORTANT: ALWAYS USE PROTEKTOR COMPLETE BEFORE APPLYING PROTEKTOR SHINE
PROTEKTOR SHINE Agent for protecting and regenerating the floor's lacquer layer	PROPERTIES: Protects a new lacquered floor from penetration by dirt and dust using a type of microfilm applied across the whole floor and on all the joints between floorboards. Eliminates minor scratches in the damaged layer of lacquer. APPLICATION: For all indoor lacquered wooden floors. <ul style="list-style-type: none"> yield approx. 100m²/ 1L IMPORTANT: BEFORE APPLYING PROTEKTOR SHINE, ALWAYS CLEAN THE FLOOR WITH PROTEKTOR COMPLETE. PROTEKTOR SHINE GENTLY INCREASES THE POLISH OF THE LACQUERED SURFACE BY SEVERAL DEGREES. DO NOT LEAVE EXCESS PROTEKTOR SHINE IN THE CREVICES OF BRUSHED AND BEVELLED FLOORBOARDS

RECOMMENDED FREQUENCY OF FLOOR MAINTENANCE*

	Protektor Concentrate	Protektor Complete	Protektor Shine
Intensity of use	Everyday cleaning	Periodic cleaning	Periodic regeneration
Floors in rooms which are not intensively used, e.g. living rooms, bedrooms	Every 5-7 days	Every 6-12 months	Visually inspect
Floors in areas which are used with average intensity, e.g. stairs, corridors, office spaces	Every 3-5 days	Every 3-6 months	Visually inspect
Floors in places which are intensively used, e.g. restaurants, shops, schools	Every 1-3 days	1-2 times per month	Visually inspect

IMPORTANT:

The floor should be cared for using only agents intended for this purpose.

Use of care agents for lacquered floors made by manufacturers other than Barlinek may result in staining, discolouration of floors or major changes to their slipperiness and sheen. Barlinek bears no responsibility for the effects of using agents made by other manufacturers.

All recommendations regarding the regularity of cleaning and caring for floors are given for reference only and depend on actual intensity of use. For these reasons they may not form the basis for warranty claims. Sand trailed or water spilt on the floor have very undesirable effects on it and it is vital to remove them. Thorough cleaning with Protektor Shine only needs to be done rarely and may be delayed considerably by regular cleaning and keeping the floor in a good condition.